

**Guidelines for Granulated Rubber Safety Tiles**  
**PLEASE READ ALL INSTRUCTIONS CAREFULLY BEFORE**  
**INSTALLATION**

You will require: An old metal scraper or similar tool (Approx. 3" wide)

A pair of sturdy rubber gloves

A sharp Stanley knife or electric jig saw

A long metal rule or other straight edge

A dry day

1. First, prepare your existing concrete or tarmac base to receive the tiles. Sweep off any debris or loose stones. Any weeds on the area should be treated with a suitable weed killer. If the area to be surfaced has moss this can usually be scraped off with a shovel. A pressure washer is an ideal way of ensuring your base work is clean
2. Allow the surface of your base to dry
3. Do not apply any adhesive; just arrange the rubber tiles into their positions dry. This will help you ascertain whether any tiles have to be cut and where the ramp edged tiles have to be placed (if required)
4. Any tiles that require shaping can be cut using your straight edge and knife or electric jigsaw. A piece of chalk may be used if necessary to mark your cuts. This can be removed with some water later
5. Lift your first tile and place to one side
6. Adhesive should be applied to the concrete or tarmac base. Using the metal scraper, apply five (5) saucer sized portions of adhesive, one portion in the middle and one in each corner on the exposed base underneath the tile you have set aside. You will find the adhesive has syrup like consistency. It is very strong, each 7Kg tub is sufficient to fix ten tiles
7. Remove the second tile in the line and replace the first; ensuring the tile makes good contact with the adhesive. At this point it is a good idea to smear a little adhesive along the adjoining edge of each tile so the tiles are not only stuck to the base but to each other for extra strength. Take care not to allow adhesive onto the face of the tile as this will look unsightly and is difficult to remove
8. Repeat steps 5, 6 & 7 over the entire area
9. It is advisable to apply adhesive along the underside of the entire length of any exposed edge of your new surface to avoid the possibility of these tiles lifting
10. Sweep off any loose bits of rubber. Allow 24 hours for adhesive to cure.